

# Preisliste 1/2004

vom 01.07.2004



Order- No.	Name	Bezeichnung Designation	Price- group	EVK (EUR)
<b>Industrieprodukte</b>				
200176	CPI-b-EE-HI-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients; 802.1x authentication; WEP+ and WPA encryption; 2 x 10BaseT, IP40 ruggedized metal housing; 2 external R-TNC connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 9V-36V DC; including 2 x external rubber antenna 2dBi; CD with software	A	649,00
200177	CPI-b-EE-HC-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients; 802.1x authentication; WEP+ and WPA encryption; 2 x 10BaseT; IP20 rail mount housing; 2 external R-SMA connectors; operating temp. -20 bis 70°C; output power 15dB; input power 9V-36V DC; including 2 x external rubber antenna 1,7dBi; CD with software	A	629,00
200178	CPI-b-ES232-HI-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients and 1 serial client, 802.1x authentication; WEP+ and WPA encryption; 1 x 10BaseT, 1 x RS232; IP40 ruggedized metal housing; 2 external R-TNC connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 9V-36V DC; including 2 x external rubber antenna 2dBi; CD with software	A	679,00
200179	CPI-b-ES232-HC-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients and 1 serial client, 802.1x authentication; WEP+ and WPA encryption; 1 x 10BaseT, 1 x RS232; IP20 rail mount housing; 2 external R-SMA connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 9V-36V DC; including 2 x external rubber antenna 1,7dBi; CD with software	A	659,00
200189	CPI-b-ES485-HI-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients and 1 serial client, 802.1x authentication; WEP+ and WPA encryption; 1 x 10BaseT, 1 x RS422/485; IP40 ruggedized metal housing; 2 external R-TNC connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 9V-36V DC; including 2 x external rubber antenna 2dBi; CD with software	A	699,00
200199	CPI-b-ES485-HC-PSI	Operating Modes: AccessClient and AccessPoint; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients and 1 serial client, 802.1x authentication; WEP+ and WPA encryption; 1 x 10BaseT, 1 x RS422/485; IP20 rail mount housing; 2 external R-SMA connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 9V-36V DC; including 2 x external rubber antenna 1,7dBi; CD with software	A	679,00
200208	CPI-b-E-HO-PAC	Operating Modes: AccessPoint and AccessClient; IEEE 802.11b, datarates 1, 2, 5, 5 and 11 Mbps; AccessClient Mode supports up to 16 ethernet clients; 802.1x authentication; WEP+ and WPA encryption; 1 x 10BaseT, IP65 outdoor housing; 2 external R-TNC connectors; operating temp. -20 bis 70°C; output power 15dBm; input power 110V-220V AC; including 2 x external rubber antenna 2dBi; CD with software	A	899,00
<b>Antennen und Zubehör</b>				
600408	ANT-RTNC.S-O-022	Standardantenne, 2,2dBi, RTNC Stecker	C	29,00
600339	ANT-TNC.KS-O-050-06-0,8m	In+Outdoor Antenne, 4,2dBi, 0,8m Kabel, TNC Stecker	C	111,00
600213	ANT-TNC.KS-O-052-03-0,8m	Fahrzeugantenne, 5,2dBi, 0,8m Kabel, TNC Stecker (benötigt Adapter 700009 oder 600269 zum Anschluß an eine ComCard)	C	79,00
600251	ANT-BRKIT-700m-3,5m	Antennenkit f. CPS-BR, Reichweite 700m, 3,5m Kabel	C	135,00
600454	ANT-TNC.KS-D-085-01-3,5m	Outdoor Patchantenne, 8,5 dBi, rechtsdrehend zirkular, TNC Buchse, 3,5m Kabel	C	183,00
600406	CAB-AC-RTNC.S-TNC.B	Adapterstück RTNC Stecker <-> TNC Buchse	C	10,00
600395	CAB-AC-RSMA.S-TNC.B	Adapterstück RSMA Stecker auf TNC Buchse	C	10,00
600234	CAB-AC-TNC.KS-TNC.KB-58-1m	Antenna cable TNC plug <-> TNC jack 1m RG58	C	32,00
600456	ACC-POW-CPI-PSI-12V-1A-W-EU	Power Supply for ComPoint Industrial, 12V, 1A, EU plug	C	28,00
600457	ACC-POW-CPI-PSI-W-UK	Power Supply for ComPoint Industrial, 12V, 1A, UK plug	C	28,00
<b>Produkt Services</b>				
DL0025	ProductService T24 für CPD-XT / CPI	Vorabaustauschservice in den ersten 2 Jahren nach Kauf: ComPoint CPD-XT / CPI Achtung: ist beim Kauf direkt mitzubestellen!	D	70,00
DL0031	ProductService T48 für CPD-XT / CPI	Vorabaustauschservice in den ersten 4 Jahren nach Kauf: ComPoint CPD-XT / CPI und Garantieverlängerung auf 4 Jahre Achtung: ist beim Kauf direkt mitzubestellen!	D	160,00